S104 SuDS Technical Appraisal Form Bio-retention



Proposed Section 104 Development at UU Reference –

Section 1 - Information required for SuDS assessment

Note: any item selected as 'not submitted' will need to be provided to support and progress the application to Technical Acceptance.

Section 1 Information required	Submitted	Not submitted	N/A	Designer Tick to highlight where information noted as 'not submitted' has now been provided
SuDS component(s) drawing / included on S104 Agreement Plan See UU S104 SuDS guidance document, comment 1 for further information				
Sectional Drawing(s)				
Completed CIRIA SuDS checklist See C753 The SuDS Manual Appendix B: Bio-retention				
Completed CIRIA SuDS health and safety checklist See C753 The SuDS Manual Appendix B: SuDS health and safety risk assessment checklist				
SuDS Component(s) Management & Maintenance document				
Maintenance inspection plan This must include access details for inspection and all maintenance requirements including machinery.				
Bio-retention sizing calculation See UU S104 SuDS guidance document, comment 4 for further information				
SuDS hydraulic assessment information See UU S104 SuDS guidance document, comment 5 for further information				
Flood route plan for any exceedance flows from the SuDS Component				
1:20 sectional catch pit manhole details				
 Landscape plan and planting schedule See UU S104 SuDS Landscape & Planting guidance document for further information 				
 Simple Index Approach (SIA) Assessment / Mitigation Indices for Water Quality (applicable for mixed use /commercial sites only) See chapter 26.7.1 of CIRIA C753 for guidance 				
Flood Risk Assessment				
Site Investigation containing geotechnical information				
Topographical survey This drawing must be a full topographical survey of the existing site, with contour to record levels at 500mm intervals as a minimum for large greenfield sites. For small/urban/very flat sites, closer level differences may be required along with spot levels for onsite surface features and changes of level.				
• S104 SuDS Technical Appraisal Form: Infiltration viability (only required if trench allows for infiltration)				

Section 2 – High level SuDS comments

Comment number	Engineer General comments	Yes	No	ТВС	Designers response comments If marked 'NO' or 'TBC', please amend the design or provide justification and mitigation of risks?
1	The component is adequately distanced from any adjacent structures/features (i.e. existing sewers, pumping station, retaining walls etc.) and does not pose a risk in relation to flooding, pollution or slope stability				
2	The topography, shape & location is suitable for the components See UU S104 SuDS guidance document, comment 2 for further information				
3	Maintenance access is acceptable for the SuDS component(s) and responsibilities detailed in management and maintenance plan (i.e. adopting body / management company) See UU S104 SuDS guidance document, comment 2 for further information				
4	The component is outside any area of significant flood risk See UU S104 SuDS guidance document, comment 3 for further information				



Section 3 — Design requirements Note: any points marked as 'No' or 'TBC' will require amendments to the design / drawings.

Bio-retention

For full design requirements, please refer to Chapter **18 of CIRIA** 753.

Hydraulics (Chapter 18.4), Maintenance (Chapter 32) & Health and safety (Chapter 36)	Yes	No	ТВС	N/A	(Designer) Tick to confirm addressed with resubmission
SuDS assessment acceptable					
Bio-retention sizing is acceptable See UU S104 SuDS guidance document, comment 4 for further information					
The component is represented correctly in the hydraulic model See UU S104 SuDS guidance document, comment 5 for further information					
Inflow velocities acceptable See UU S104 SuDS guidance document, comment 5 for further information					
Suitable head loss' applied in the model See UU S104 SuDS guidance document, comment 5 for further information					
Perforated pipes sufficiently sized for design event flows (2yr event) See UU S104 SuDS guidance document, comment 5 for further information					
Depth of temporary storage acceptable See UU S104 SuDS guidance document, comment 5 for further information					
Flow control outlet diameter acceptable See UU S104 SuDS guidance document, comment 5 for further information					
Inlet discharge level acceptable Must freely in 2yr event, or the surcharge risks justified					
Maximum water level acceptable Must be at least 500mm below the lowest FFL of any adjacent properties					
Drain down time acceptable See UU S104 SuDS guidance document, comment 5 for further information					
The flood routing for exceedance flow is acceptable See UU S104 SuDS guidance document, comment 5 for further information					
Slope gradients acceptable See UU S104 SuDS guidance document, comment 6 for further information					
Effective pre-treatment has been provided See UU S104 SuDS guidance document, comment 7 for further information					
Erosion protection / energy dissipation measures acceptable See UU S104 SuDS guidance document, comment 8 for further information					
Inlet and outlet connection details acceptable See UU S104 SuDS guidance document, comment 9 for further information					
Overflow / underdrain design acceptable See UU S104 SuDS guidance document, comment 10 for further information					
Construction layers acceptable See UU S104 SuDS guidance document, comment 11 for further information					
Planting and vegetation proposals are acceptable See UU S104 SuDS Landscape & Planting guidance document for further information					
The base of the component is set 1m above groundwater levels					
Liner specification is acceptable See UU S104 SuDS guidance document, comment 12 for further information					

Section 4 – Drawing requirements

S104 Agreement Plan and Land Registry Plan requirements	Yes	No	ТВС	N/A	(Designer) Tick to confirm addressed with resubmission
Both drawings contain all relevant component information?					
Component offered for adoption is coloured purple					
A 2m easement is be applied from the top of the embankment and around the full perimeter of the component, coloured in yellow and dimensioned					
The following requirements are relevant to the S104 Agreement Plan only;				1	
Bio-retention component type noted correctly (i.e. bio-retention swale, anaerobic system or infiltration)					
Dimensions shown (length at longest point in addition to the width at widest point, both at the bottom and top of the component)					
The area of the component (m²), max water depth (m) and storage volume (m³) are noted on the drawing					
The inlet level and outlet level are to be clearly noted, in addition to the top of bank level and bed level					
Component area (m²) and depth (m) matches the hydraulic model					
Base & side slope gradients labelled, clearly falling to the outlet					
Borehole locations shown					
Full design detail shown See UU S104 SuDS guidance document, comment 13 for further information					
Erosion protection measures detailed at inlet points					
Ancillaries are clearly identified (i.e. catch pit manholes and flow control manholes)					
Sectional view drawing	Yes	No			
Maximum water levels for the following storm events; 2, 30, 100 & 100+cc year events, For sites with Pumping Stations, the 200 year water level also needs to be noted to confirm compliance with Design & Construction Guidance (D5.1.2)					
The inlet level and outlet level are to be clearly noted, in addition to the top of bank level and bed level					
Slope gradients shown					
Erosion protection measures detailed at inlet points					
Full design detail shown including materials See UU S104 SuDS guidance document, comment 13 for further information					